



estefold 2300

The Offline Folding Standard

**estefold 2300's proven, industry standard setting,
unique adjectives are:**

- Most accurate folds
- Highest reliability
- Extremely long lifetime

○ table up



○ table down



Features

estefold 2300 is characterized by a clear, digital display, an outstanding reliability and an extra wide feed table in a convenient working height which eases the manual feed.

Only a few minutes practice are sufficient to utilize its full potential.

The integrated service program enables time saving test runs and a fast error diagnosis. The fold speed of 19 m/min is the fastest in its class.

Technical Data

Passes for full fold	2
Folding speed	19 m/min
Document length (Fan Fold only)	400 mm - unlimited
Document length (Fan- and Cross fold)	400 - 2100 mm (80g/m ² DIN)
Media width	100 - 930 mm
Media weight	60 - 120 g/m ²
Panel width	180 - 420 mm*
Panel height	200 - 420 mm
Margin	0 - 30 mm
Fold programs	10**

Options

Fold Away Feed Table

The Fold Away Feed Table offers the advantage that it can be easily flipped down when the estefold 2300 is not in use. The footprint is therefore reduced by approx. 50%.

Narrow Fold 10 cm

It enhances the foldable panel width to 100 - 420 mm which allows maps to be folded to their standard format. Hiking-, biking- or city maps can be created fast and dependable in individual volumes.

Adjustable feet

The adjustable feet allow for a simple levelling of the folder on uneven floors. They are supplied with the folder, in addition to the factory-mounted rolls, and must be screwed on in place of the rolls on site.

* Optional 100 - 420 mm

** 4 pre-programmed-, 6 editable fold programs (calculated and uncalculated)